

**FUEL SYSTEM**

POS.	CODE	DESCRIPTION	Qty
1	9371.100	bleeding pipe mm 536	1
1	9371.101	bleeding pipe mm 745	1
1	9571.069	bleeding pipe mm 1350	1
1b	9371.101	bleeding pipe mm 745	1
2	4670.058	copper gasket diam. 8,2X12X1,5	1
3	1901.029	union bolt M 8	1
4	4670.058	copper gasket diam. 8,2X12X1,5	1
5	1901.029	union bolt M 8	1
6	3616.082	fuel tank strap	2
7	9043.092	fuel tank cap	1
8	9043.025	fuel tank cap	1
9	9761.001	screw M 4 X 0,7 X 12	6
10	4776.040	gasket	1
11	5055.023	plate	1
12	4906.008	fuel gauge (mm 193) 15/29 lt	1
13	3790.074	injector top plate	2
14	3203.050	selflocking nut M 6	4
15	7625.010	washer diam. 8	4
16	6760.045	stud M 6 X 65 (80)	4
17	9376.060	high press.pipe	1
18	4670.058	copper gasket diam. 8,2X12X1,5	1
20	9730.115	screw M 5 X 14	2
21	3616.018	injector feed pipe saddle	2
22	5400.046	rubber sheathing	2
23	9730.139	screw M 6 X 60	2
24	1557.019	drilled block	2
25	1557.020	threaded block	2
26	8102.085	FUEL TANK 10 lt (410X190X140)	1
26	8103.046	FUEL TANK 7 lt (370X170X140)	1
27	8103.021	fuel tank 15 liters	1
28	<----->	lockpin	0
29	6615.045	NOZZLE-HOLDER Bosch	2
30	6531.104	nozzle	2
31	<----->	gasket	0
32	4670.005	copper gasket 0,50	2
32	4670.006	copper gasket 1,00	2
32	4670.065	copper gasket 1,50	2
33	7301.006	connection	2
34	9376.061	high press.pipe	1
35	3616.085	fuel tank strap mm 625	2
35	3617.077	fuel tank strap mm 592	2
36	9600.057	rubber spacer	4
37	8315.016	rubber shim	1
38	8042.024	fuel tank saddle	1
39	3586.058	electric valve	1
40	3440.055	QSD STOP DEVICE	1
41	3617.214	fuel tank strap mm 345	2
42	7265.008	connection	2
43	1200.031	rubber oil seal	2
44	4701.006	gasket	1
45	8866.018	support	1
46	7470.003	filler	2
47	8335.029	washer seal	2

Group: 12LD
Engine: 12LD 435-2 Drawing: E

FUEL SYSTEM			
POS.	CODE	DESCRIPTION	Qty
48	5755.034	valve spring	2
49	3730.036	FUEL FILTER	1
50	9372.034	fuel hose (mm 630)	1
50	9375.013	f.hose mm 2030	1
50	9375.032	fuel hose mm 336	1
50	9375.060	fuel hose mm 850	1
50b	9375.142	fuel hose mm 1100	1
51	4760.015	valve gasket	2
52	6578.042	injection plunger	2
53	9730.100	screw M 8 X 25	3
54	7625.010	washer diam. 8	4
55	9672.012	delivery valve BOSCH	2
56	8400.048	taper pin	1
57	1901.031	union bolt M 12	1
58	1901.101	union bolt l=60	1
59	3730.121	fuel filter	1
60	1901.171	deaeration plug	1
61	4775.196	gasket	1
61a	4670.062	copper gasket diam. 6,2 X 10 X 1,5	2
62	1901.171	deaeration plug	1
62a	1901.033	union bolt M 6	1
63	4670.060	copper gasket diam.12	2
65	9730.139	screw M 6 X 60	2
66	1901.033	union bolt M 6	1
67	4670.062	copper gasket diam. 6,2 X 10 X 1,5	3
68	5575.006	spring	1
69	3930.019	cup	1
70	1200.268	rubber oil seal	1
71	2175.009	fuel filter cartridge	1
71	3730.015	FUEL FILTER	1
72	4490.017	gasket	1
73	4430.071	gasket	1
74	6370.515	tank plate	1
75	8636.001	vibration-damping	4
76	9043.092	fuel tank cap	1
77	8866.067	support	2
78	4701.029	rubber shim	2
79	9245.076	stay bolt	4
80	8760.038	fuel filter support	1
81	2175.045	fuel filter cartridge	1
84	«-----»	injection pump	0
86	4580.002	gasket 0,10	1
86	4580.009	gasket 0,50	1
86	4580.068	gasket 0,05	1
86	4580.193	gasket 0,30	1
87	1580.023	bushing	1
88	771R.001	washer diam. 5,3	1
89	9375.351	fuel hose (mm 190)	1
89a	9375.005	hose mm 235	1
90	2800.003	cotter pin	1
91	7270.104	banjo union diam.10	1
92	3587.103	el.valve (12V)on injection pump	1
92	3587.109	el.valve (24V)on injection pump	1

Group: 12LD
Engine: 12LD 435-2 Drawing: E

FUEL SYSTEM			
POS.	CODE	DESCRIPTION	Qty
93	1901.040	union bolt M 12	1
94	4670.060	copper gasket diam.12	2
95	9375.005	fuel hose	1
96	9571.207	bleeding pipe (KAESER)	1
98	2605.033	filter cover	1
99	1202.052	rubber oil seal	1
100	1760.162	bolt	1
101	3630.008	clamp	1
102	1901.032	union bolt M 14	1
103	4670.061	copper gasket diam.14	2
104	4850.009	guide	1
105	7980.020	cup	2
106	«-----»	injector rack	0
109	1901.030	union bolt M 10	1
110	7200.078	drive rod	1
111	4670.059	copper gasket diam.10	2
112	«-----»	sleeve (no longer avail.)	0
113	6230.069	pin	1
114	9375.276	fuel hose mm 430	1
114	9375.308	fuel pipe mm 2000	1
114	9375.721	fuel pipe mm 850	1
114	9375.859	del.pipe mm 1000	1
115	9375.276	fuel hose mm 430	1
116	3587.105	el.valve 12V on engine	1
117	4670.059	copper gasket diam.10	4
118	8103.308	FUEL TANK (29 liters)	1
119	4701.030	rubber shim	2
120	8866.066	support	2
121	8635.059	vibration-damping	4
122	9220.024	fuel filter head	1
123	2175.053	fuel filter cartridge	1
125	3730.151	fuel filter	1
126	2175.046	fuel filter cartridge	1
127	5625.002	spring	2
128	4670.061	copper gasket diam.14	2
129	1901.032	union bolt M 14	1
130	6230.068	pin	2
131	«-----»	spring retainer bottom - see Pos. E 84	0
132	7215.017	tappet	2
133	«-----»	roller (no longer avail.)	0
136	1200.087	O ring 3150	1
137	6780.008	stud M 8 X 20 (32)	2
138	9375.022	fuel hose(mm 2000)	1
138	9375.029	fuel hose(mm 835)	1
138	9375.690	hose mm 220	1
138	9375.853	fuel pipe mm 1000	1
138	9375.854	hose mm 680	1
139	6585.079	feed pump	1
140	1901.030	union bolt M 10	1
141	4670.059	copper gasket diam.10	2
142	3240.164	nut M 8	2
143	9375.908	fuel hose	1
144	1901.030	union bolt M 10	2

Group: 12LD
Engine: 12LD 435-2 Drawing: E

FUEL SYSTEM			
POS.	CODE	DESCRIPTION	Qty
145	1557.019	drilled block	2
146	1557.020	threaded block	2
147	3521.043	spacer	2
148	6780.016	stud M 8 X 28 (40)	2
149	3240.018	nut M 8	2
150	8315.016	gasket	1
151	7625.012	washer diam. 8,4	2
152	7565.007	washer diam. 8	2
153	8865.193	support	1
154	1770.056	bolt M 8 X 1,25 X 18	2
155	7565.007	washer diam. 8	2
156	1901.029	union bolt M 8	1
157	1901.152	union bolt M 12 l=51	1
158	8866.092	tank support	1
159	8900.318	electro-magnet support	1
160	5140.014	panel	1
162	9375.896	pipe	1
162	9375.945	hose from feed pump to QSD device mm 1000	1
163	9373.044	f.hose mm 235	1
163	9375.856	fuel hose mm 1030	1
172	5801.037	spring	1
173	8245.003	gov.ball diam. 4,8 3/16''	1
174	7555.029	washer diam. 8	2
175	7625.012	washer diam. 8,4	2
176	7565.007	washer diam. 8	2
177	3240.018	nut M 8	2

